IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Continuation of Serial No. 09/172,962

Applicant:

Yoichiro SAKO, et al.

U.S. Serial No.:

Filed Concurrently Herewith

Title of Invention:

SIGNAL RECORDING/REPRODUCING METHOD
AND APPARATUS, SIGNAL RECORD MEDIUM AND

SIGNAL TRANSMISSION/RECEPTION METHOD

AND APPARATUS

Examiner

H. Nguyen

Art Unit

2615

745 Fifth Avenue New York, NY 10151

EXPRESS MAIL

Mailing Label Number:

EV001420211US

Date of Deposit:

November 2, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" Service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, DC 20231.

(Typed or printed name of person mailing paper or fee)

(Signature of person mailing paper or fee)

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Box Patent Application (35 U.S.C. 111) Washington, D.C. 20231

Sir:

Before the issuance of the first Office Action, please amend the above-identified application as follows:

IN THE SPECIFICATION:

Please add the following as the first paragraph on page 1 of the specification:

--This is a continuation of application Serial No. 09/172,962 filed October 14, 1998 which is a divisional of application Serial No. 08/698,089, filed August 15, 1996.--

IN THE CLAIMS:

Please cancel claims 1-72.

Please add new claims 73-88 as follows:

73. A signal encoding method characterized by:

detecting a high signal level portion of a video signal and/or audio signal in a predetermined time interval; and

inserting an identification signal relevant to the video signal and/or audio signal only within a low signal level portion temporally before or after the detected high level portion of the video signal and/or audio signal.

- 74. A signal encoding method as claimed in claim 73, wherein said identification signal is inserted into the video signal and/or audio signal in such a configuration as to be detectable on statistical processing of the video signal and/or audio signal.
- 75. A signal encoding method as claim in claim 74, wherein said identification signal is inserted into least significant bits of samples of the video signal and/or audio signal.
- 76. A signal recording method comprising:

detecting a high signal level portion of a video signal and/or audio signal in a predetermined time interval;

inserting an identification signal relevant to the video signal and/or audio signal only within a low signal level portion temporally before or after the detected high level portion of the video signal and/or audio signal; and

recording the video signal and/or audio signal, into which said identification signal has been inserted, on a signal record medium.

77. A signal encoder characterized by:

detecting means for detecting a high signal level portion of a video signal and/or audio signal in a predetermined time interval; and

inserting means for inserting an identification signal relevant to the video signal and/or audio signal only within a low signal level portion temporally before or after the detected high level portion of the video signal and/or audio signal.

- 78. A signal encoder as claimed in claim 77, wherein said identification signal is inserted into the video signal and/or audio signal in such a configuration as to be detectable on statistical processing of the video signal and/or audio signal.
- 79. A signal encoder as claimed in claim 78, wherein said identification signal is inserted into least significant bits of samples of the video signal and/or audio signal.
- 80. A signal recording apparatus comprising:

detecting means for detecting a high signal level portion of a video signal and/or audio signal in a predetermined time interval;

inserting means for inserting an identification signal relevant to the video signal and/or audio signal only within a low signal level portion temporally before or after the detected high level portion of the video signal and/or audio signal; and

recording means for recording the video signal and/or audio signal, into which said identification signal has been inserted, on a signal record medium.

81. A signal transmitting method comprising:

detecting a high signal level portion of a video signal and/or audio signal in a predetermined time interval;

inserting an identification signal relevant to the video signal and/or audio signal only within a low signal level portion temporally before or after the detected high level portion of the video signal and/or audio signal; and

transmitting the video signal and/or audio signal into which said identification signal has been inserted.

82. A record medium comprising:

a program management area or table of contents area, and a program area including an audio signal and/or a video signal;

wherein an identification signal relevant to the video signal and/or audio signal is inserted therein only within a low signal level portion temporally before or after the detected high level portion of the video signal and/or audio signal in a predetermined time interval.

- 83. The record medium as claimed in claim 82, wherein said identification signal is inserted into the video signal and/or audio signal in such a configuration as to be detectable on statistical processing of the video signal and/or audio signal.
- 84. The record medium as claimed in claim 83, wherein said identification signal is inserted into least significant bits of samples of the video signal and/or audio signal.

85. The record medium as claimed in claim 82, wherein said record medium is an optical disc that has a center aperture, a lead-in area, a program area and end area, and wherein the program management area or table of contents area are located on the lead-in area.

86. The record medium as claimed in claim 85, wherein said optical disc is CD, CD-ROM, or DVD.

87. The record medium as claimed in claim 82, wherein said record medium is a semiconductor record medium, magnetic disc or a tape-shaped record medium.

88. The record medium as claimed in claim 82, wherein the video signal and/or audio signal is encoded or modulated in accordance with MPEG1 standard, MPEG 2 standard, an adaptive transform acoustic coding (ATRAC), or a PCM.--

REMARKS

This preliminary amendment makes reference to the parent application and cancels those claims that are being prosecuted in the parent. New claims 73-80 have been added. These claims are the same as those cancelled by the Examiner in the parent application as being directed to a different invention.

Entry of the above amendatory matter and early examination on the merits are respectfully requested.

Respectfully submitted,

FROMMER LAWRENCE & HAUG LLP Attorneys for Applicant

Bv.

William S. Frommer

Reg. No. 25,506 Tel. (212) 588-0800